

J22270 | TRUE fibre Matt 200

SPECIAL-COATED MATT PAPER

PRODUCT SPECIFICATION *

Weight DIN EN ISO 536	g/m ²	203	± 7
Thickness DIN EN ISO 534	µm	303	± 15
	mil	11.9	± 0.6
Colour Elrepho UVO (D65) ISO 2469	L	97,8	± 1,0
	a	0,2	± 0,5
	b	2,35	± 1,0
	delta b	-0,7	± 0,8
CIE whiteness (D65/10°) min. ISO 2469		> 78	
Opacity min. ISO 2469	%	> 93	

BENEFITS & PROPERTIES

- Smooth surface
- Pin-sharp details
- Vivid colours
- High colour consistency and gamut
- Made from alpha cellulose
- Meets criteria for permanence according ISO 9706

KEY APPLICATIONS

Professional Photo & Fine Art

- High-end photo prints
- Portfolio folders
- Exhibitions
- Professional photo albums
- Black and white photography

Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Printability

Simplex printable

Printing Technology

💧 Inkjet water-based

Compatibility

Can be used on all commercial thermal, piezo water-based printing systems like Epson, Canon, Hewlett-Packard, Kodak, Encad etc.

Certificates



Fogra 29109



DIN EN ISO 9706

Version 02/2016